

LED strip 14K-WP-K-0960-24V

Ref. KWP-14K-0960-24

Ref. arch 14K-WP-K-0960-24V

NEW



Dimensions: Width [W]: 16.7 mm | Max run length [L]: 10 m | Cut every [C]: 50 mm | LED spacing [D]: 6.25 mm | Height [H]: 4.6 mm



- CRI 90+
- Superior color consistency and dimming performance
- Smooth regulation of brightness
- Clean line of light when paired with most KLUŚ extrusions and LIGER cover
- High light transmission of the silicone sleeve (over 93%)

ADDITIONAL INFORMATION

- NOTE! LED tapes in a silicone sleeve, with a degree of protection IP65 are made to the size specified by the customer only by KLUŚ - if you cut it yourself, the tape will become unsealed, which will result in the loss of the warranty
- the luminous flux applies to unsealed LED strip

TECHNICAL SPECIFICATIONS

IP protection rating	65
Sealing type	silicon sleeve
CRI	90
LxBy	L80B50
Lifetime	60000 h
Working temperature	-20°C - 60°C
Input voltage	24 V DC
Power consumption	9.6 W/m
Beam angle	120°
MacAdam's ellipse	3 SDCM
Number of LEDs per 1 m	140
Number of LEDs per cut section	7 pcs
Energy consumption	10 kWh/1000h
Warranty [months]	84
Klasa energetyczna	A

Color temperature	Lumen output	Efficiency	Ref
2700 K	1090 lm/m	113 lm/W	KWP-14K27-0960-24 14K-WP-K-27-0960-24V
3000 K	1125 lm/m	117 lm/W	KWP-14K30-0960-24 14K-WP-K-30-0960-24V
3500 K	1150 lm/m	119 lm/W	KWP-14K35-0960-24 14K-WP-K-35-0960-24V
4000 K	1195 lm/m	124 lm/W	KWP-14K40-0960-24 14K-WP-K-40-0960-24V
5000 K	1185 lm/m	123 lm/W	KWP-14K50-0960-24 14K-WP-K-50-0960-24V