

Profile 3035-KR-KOZE

Ref. A01780

Ref. arch C1780



- Mounting track
- Component of the mounting track
- Edge profile to be adhered and covered with plaster

APPLICATION

- building openwork mounting tracks for lighting fixtures

MOUNTING


- combined with bridges, using dedicated accessories

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING

1:2



TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver non anodized
Width	24.8 mm
Height	24 mm
Building type	Commercial, Residential, HoReCa object, Retail, Entertainment/ Arts
Facility zone	industrial and technical
Can be easily connected into runs	yes
Mounting to drywall	yes
To cover with plaster	yes


Length	Ref
1000 mm	A01780N_1 C1780NA_1
2005 mm	A01780N_2 C1780NA_2
3010 mm	A01780N_3 C1780NA_3

Profile 3035-KR-KOZE

Ref. A01780

Ref. arch C1780

RELATED PROFILES > MOUNTING TRACKS



RAM-3035-KOZE

A18056

Ref. arch 18056