

Cover FOLED

Ref. B17045S, B17045C

Ref. arch 17047, 17045



APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- ATTENTION! rigid cover, not intended for bending or deformation
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	PMMA
Shape	flat (embedded in the fixture)
Maximum length on request	6000 mm
Width	26.9 mm
Possibility of obtaining a line of light	yes
UV resistance	yes

Color	Length	Light transmission	Ref
☐ frosted	1000 mm	78 %	B17045S_1 17047_1
	2005 mm		B17045S_2 17047_2
	3010 mm		B17045S_3 17047_3
■ black	1000 mm	39 %	B17045C_1 17045_1
	2005 mm		B17045C_2 17045_2
	3010 mm		B17045C_3 17045_3

Cover FOLED


Ref. B17045S, B17045C

Ref. arch 17047, 17045

RELATED PROFILES > STRETCH CEILINGS



FOLED
A08332V1
Ref. arch B8332V1



FOLED-BOK
A08334V1
Ref. arch B8334V1



FOLED-SUF
A08333V1
Ref. arch B8333V1