

# Profile HR-MAX-T

Ref. A01827

Ref. arch C1827



- Mounting track
- Easy servicing of the HR-MAX Profile
- For indoor | outdoor ground installation
- Compatibility with the HR-MAX-TW mounting track
- High mechanical resistance

## APPLICATION

- makes mounting and service of the HR-MAX profile easy

## MOUNTING


- in the ground, with mounting adhesive
- can be easily connected into runs and systems
- possibility to connect to the HR-MAX-TW profile to make a mounting track with sections for cables and accessories at intervals

## ADDITIONAL INFORMATION


- in order to protect the lighting fixture during installation, a TECH-35 protective insert should be used
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance  $+ 5$  mm); for selected covers: 6050 mm, 10050 mm (tolerance  $+ 5$  mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING

1:2



## TECHNICAL SPECIFICATIONS

Material	aluminum
Color	 silver non anodized
Profile cross-section	rectangular
Width	37.6 mm
Height	29.2 mm
Building type	Outdoor, Commercial, Retail
Facility zone	communication routes and corridors, wejścia i bramy, parking i garaż, driveways
Can be easily connected into runs	yes

Length	Ref
1000 mm	A01827N_1 C1827NA_1
2005 mm	A01827N_2 C1827NA_2
3010 mm	A01827N_3 C1827NA_3

# Profile HR-MAX-T

Ref. A01827

Ref. arch C1827

**KLUŚ** Inspiring  
Solutions

## SAMPLE PROJECTS



## RELATED PROFILES > FOR FLOORS



### HR-MAX

A01829

Ref. arch C1829

## RELATED PROFILES > MOUNTING TRACKS





### HR-MAX-TW

A01828

Ref. arch C1828

## RELATED ACCESSORIES > RELATED END CAPS

NAME		MATERIAL	COLOR	REF.
HR-MAX-T-STN	<b>NEW</b>	 stainless steel	 silver	C28021N00 24389

## RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > ADDITIONAL ITEMS

# Profile HR-MAX-T

Ref. A01827

Ref. arch C1827

**KLUŚ** Inspiring  
Solutions



CLIP

**HR-MAX**

C28059C00

Ref. arch 24416

---

## RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > TECHNICAL AND PROTECTIVE INSERTS



PROTECTIVE INSERT

**TECH-35**

C24534C02

Ref. arch 17127