Profile HR-MAX-TW Ref. A01828


Ref. arch C1828







1:2









- Mounting track
- Easy servicing of the HR-MAX Profile
- For indoor outdoor ground installation
- Cable management space
- Compatibility with the HR-MAX-T mounting track
- High mechanical resistance

APPLICATION

- makes mounting and service of the HR-MAX profile easy

MOUNTING

- in the ground, with mounting adhesive
- can be easily connected into runs and systems
- possibility to connect to the HR-MAX-TW profile to make a mounting track with sections for cables and accessories at intervals

ADDITIONAL INFORMATION

- in order to protect the lighting fixture during installation, a TECH-35 protective insert should be used
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL SPECIFICATIONS

Material	aluminum	
Color	silver non anodized	
Profile cross-section	rectangular	
Width	37.6 mm	
Height	55 mm	
Corrosion resistance at high salinity	yes	
Building type	Outdoor, Commercial, Retail	
Facility zone	communication routes and corridors, wejścia i bramy, parking i garaż, driveways	
Can be easily connected into runs	yes	
Wire out end cap	yes	

Length	Ref				
1000 mm	A01828N_1 C1828NA_1				
2005 mm	A01828N_2 C1828NA_2				
3010 mm	A01828N_3 C1828NA_3				

Profile HR-MAX-TW Ref. A01828

Ref. arch C1828

SAMPLE PROJECTS





RELATED PROFILES > FOR FLOORS



HR-MAX A01829 Ref. arch C1829

RELATED PROFILES > MOUNTING TRACKS



HR-MAX-T A01827 Ref. arch C1827

RELATED ACCESSORIES > RELATED END CAPS

NAME			MATERIAL	COLOR	REF.
HR-MAX-TK-STN	NEW	.0.11	stainless steel	silver	C28023N00 24391
HR-MAX-T-STN	NEW	11	stainless steel	silver	C28021N00 24389

Profile HR-MAX-TW Ref. A01828

Ref. arch C1828



RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > ADDITIONAL ITEMS



CLIP HR-MAX C28059C00 Ref. arch 24416

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > TECHNICAL AND PROTECTIVE INSERTS



PROTECTIVE INSERT TECH-35 C24534C02 Ref. arch 17127