

APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	PMMA
Shape	semicircular
Maximum length on request	6000 mm
Width	9 mm
Possibility of bending	yes
UV resistance	yes

Color	Length	Light transmission	Possibility of obtaining a line of light	Ref
<input type="checkbox"/> frosted	1000 mm	63 %	yes	B17164M_1 17164_1
	2005 mm			B17164M_2 17164_2
	3010 mm			B17164M_3 17164_3
<input checked="" type="checkbox"/> black	1000 mm	42 %	no	B17064C_1 17088_1
	2005 mm			B17064C_2 17088_2
	3010 mm			B17064C_3 17088_3
<input checked="" type="checkbox"/> semi-transparent	1000 mm	87 %	no	B17064F_1 17090_1
	2005 mm			B17064F_2 17090_2
	3010 mm			B17064F_3 17090_3

Cover LUK-10

Ref. B17164M, B17064C, B17064F

Ref. arch 17164, 17088, 17090

RELATED PROFILES > MINIMALISTIC



PIKO-O
A01167
Ref. arch C1167