

# Profile NIBO Ref. A18010

Ref. arch 18010



## **TECHNICAL DRAWING**



# **TECHNICAL SPECIFICATIONS**

Material	aluminum
Color	silver anodized
Possible fixture IP	20
Possible fixture shapes	rectangular
Profile cross-section	rectangular
Width	49.9 mm
Height	52 mm
Compartment for power supply	yes
Building type	Other, Commercial, Residential, HoReCa object
Facility zone	office, communication routes and corridors, parking i garaż, industrial and technical, conference room
Wire out back of extrusion	yes

Length	Ref
1000 mm	A18010A_1 18010ANODA_1
2005 mm	A18010A_2 18010ANODA_2
3010 mm	A18010A_3 18010ANODA_3



- Mounting track
- Space for power supply and electronic components
- Easy maintenance

#### APPLICATION

- mounting of power supplies and electronic components

## MOUNTING

- to the surface, using a dedicated mounting track and properly selected screws

#### ADDITIONAL INFORMATION

- the power supply can be secured inside the profile using dedicated accessories
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm /
- 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm) - when choosing a different length of profiles / covers than available in the standard, you
- should additionally choose the cutting service at KLUŚ





SAMPLE PROJECTS





# **RELATED ACCESSORIES > RELATED END CAPS**

NAME	MATERIAL	COLOR	REF.
NIBO	PP	gray	C24001C02 24001

#### RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONDUCTIVE FASTENERS AND HEADS FOR SURFACE



W-BOX-Z C28253N00 Ref. arch 00643

## **RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER**



GLAND 6x1,2 C24517C07 Ref. arch 00802



RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > TECHNICAL AND PROTECTIVE INSERTS







MOUNTING PAD 45 Z70457 Ref. arch 70457