
Ref. arch B8288

























- Minimum width and height
- Small bending radius

APPLICATION

- furniture and decorative lighting

MOUNTING

- to the surface, suspended or recessed, using dedicated accessories, with double-sided adhesive tape or mounting adhesive
- easy assembly and disassembly by snapping in and out

ADDITIONAL INFORMATION

- for suspending small-size profiles, it is recommended to use a wire with a diameter of 0.5 $\,$ mm $\,$
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL SPECIFICATIONS

| Material | aluminum | | |
|--|---|--|--|
| Possible fixture IP | 20, 67 | | |
| Possible fixture shapes | rectangular | | |
| Profile cross-section | rectangular | | |
| Width | 10 mm | | |
| Height | 7 mm | | |
| LED gluing width A | 7 mm | | |
| Possibility of twisting | yes | | |
| Possibility of bending | yes | | |
| Minimum external radius | 150 mm | | |
| Minimum internal radius | 150 mm | | |
| Building type | Residential, Commercial, Retail | | |
| Facility zone | furniture, bathroom, kitchen, office, advertising / POS, stairs and handrails | | |
| Easy assembly and disassembly by snapping in and out | yes | | |
| The cover is cut to the length of the profile | yes | | |
| Wire out end cap | yes | | |

| Color | Length | Ref |
|-----------------|---------|---------------------------------|
| | 1000 mm | A08288A_1 B8288ANODA_1 |
| silver anodized | 2005 mm | A08288A_2 B8288ANODA_2 |
| | 3010 mm | A08288A_3 B8288ANODA_3 |
| | 1000 mm | A08288A07_1 B8288K7_1 |
| black anodized | 2005 mm | A08288A07_2 B8288K7_2 |
| | 3010 mm | A08288A07_3 B8288K7_3 |

Ref. arch B8288



| Wire out back of extrusion | yes |
|----------------------------|-----|

SAMPLE PROJECTS







RELATED ACCESSORIES > RELATED COVERS

| NAME | MATERIAL | MATERIAL TRANSMITTANCECOLOR | | REF. |
|-------------|----------|-----------------------------|-----------|------------------|
| BENCO-7 NEW | silikon | 58 % | ☐ frosted | B17069M 17069 |
| PIKO | РММА | 57 % | frosted | B17034M 17034 |

RELATED ACCESSORIES > RELATED END CAPS

| NAME | | MATERIAL | COLOR | REF. |
|----------|---|----------|-------|----------------------|
| PIKO | | ABS | gray | C24202C02 24202 |
| | | | black | C24202C07 24379 |
| PIKO-OTW | 4 | ABS | gray | C24202C02TW 24299 |
| | | | black | C24202C07TW 24399 |

RELATED ACCESSORIES > RELATED LED > ULTRATHIN







K-1091-24V K-1091-24 Ref. arch K-1091-24V

RELATED ACCESSORIES > RELATED LED > WHITE MONO



5K-WP-K-1091-24V KWP-5K-1091-24 Ref. arch 5K-WP-K-1091-24V

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > FASTENERS AND HEADS FOR PROFILES



FASTENER
K-10-PP
C28235N00
Ref arch 42670



FASTENER
K-10-WL
C28237N00
Ref. arch 42672



FASTENER
K-10-WP
C28236N00
Ref. arch 42671

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > MOUNTING BRACKETS



MOUNTING BRACKET **K-10** C24340C00 Ref. arch 24340





RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER



GLAND **6x1,2** C24517C07 Ref. arch 00802