

LED strip WP-K-1530-RGB+W-24V

Ref. KWP-RGBW-1530-24

Ref. arch WP-K-1530-RGB+W-24V



Dimensions: Width [W]: 12 mm | Max run length [L]: 6 m | Cut every [C]: 62.5 mm | LED spacing [D]: 10 mm | Height [H]: 4 mm



- UL Listed certification
- 3-Step MacAdam's ellipse, single binning (applies only to white color)
- High light transmission of the silicone sleeve (over 93%)

ADDITIONAL INFORMATION

- NOTE! LED tapes in a silicone sleeve, with a degree of protection IP65 are made to the size specified by the customer only by KLUŚ - if you cut it yourself, the tape will become unsealed, which will result in the loss of the warranty
- the luminous flux applies to unsealed LED strip

TECHNICAL SPECIFICATIONS

IP protection rating	65
Sealing type	silicon sleeve
LED color	RGB+W
CRI	90
Only valid for white	yes
LxBy	L80B50
Lifetime	60000 h
Working temperature	-20°C - 60°C
Input voltage	24 V DC
Power consumption	15.3 W/m
Beam angle	120°

Number of LEDs per 1 m	384
Number of LEDs per cut section	24 pcs
Energy consumption	4 kWh/1000h
Warranty [months]	48
Klasa energetyczna	G

Color temperature	Lumen output	Efficiency
3000 K	252 lm/m	16 lm/W
RED	48 lm/m	3 lm/W
GREEN	330 lm/m	21 lm/W
BLUE	68 lm/m	4 lm/W