

LED strip WP-K-SE-BLUE-1210-8-24V

Ref. KWP-SEBLUE-1210-24-8

Ref. arch WP-K-SE-BLUE-1210-8-24



Dimensions: Width [W]: 10 mm | Max run length [L]: 6 m | Cut every [C]: 100 mm | LED spacing [D]: 16.7 mm | Height [H]: 4 mm



- Side emitting LED strip
- UL Listed certification
- High light transmission of the silicone sleeve (over 93%)

ADDITIONAL INFORMATION

- NOTE! LED tapes in a silicone sleeve, with a degree of protection IP65 are made to the size specified by the customer only by KLUŚ - if you cut it yourself, the tape will become unsealed, which will result in the loss of the warranty
- the luminous flux applies to unsealed LED strip

TECHNICAL SPECIFICATIONS

IP protection rating	65
Sealing type	silicon sleeve
LED color	BLUE
Working temperature	-20°C - 60°C
Input voltage	24 V DC
Power consumption	4.8 W/m
Beam angle	120°

MacAdam's ellipse	3 SDCM
Number of LEDs per 1 m	60
Number of LEDs per cut section	6 pcs
Energy consumption	5 kWh/1000h
Warranty [months]	48

Lumen output	Efficiency
198 lm/m	41 lm/W