



Polar diagram



Cone diagram



UGR diagram

Glare evaluation according to UGR													
p Ceiling	70	70	50	50	30	70	70	50	50	30			
p Walls	50	30	50	30	30	50	30	50	30	30			
p Floor	20	20	20	20	20	20	20	20	20	20			
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis							
2H	2H	11.9	12.9	12.2	13.1	13.3	21.4	22.5	21.7	22.7	22.9		
	3H	12.3	13.3	12.6	13.5	13.8	21.8	22.7	22.1	23.0	23.2		
	4H	12.6	13.4	12.9	13.7	14.0	21.9	22.7	22.2	23.0	23.3		
	6H	12.9	13.7	13.2	14.0	14.3	21.9	22.7	22.2	23.0	23.3		
	8H	13.1	13.8	13.4	14.1	14.4	21.9	22.6	22.2	22.9	23.2		
	12H	13.3	14.0	13.6	14.3	14.6	21.8	22.6	22.2	22.9	23.2		
4H	2H	12.4	13.2	12.7	13.5	13.8	21.3	22.1	21.6	22.4	22.7		
	3H	13.0	13.7	13.4	14.0	14.4	21.7	22.4	22.0	22.7	23.0		
	4H	13.4	14.0	13.7	14.3	14.7	21.8	22.4	22.2	22.8	23.1		
	6H	13.8	14.4	14.2	14.7	15.1	21.8	22.4	22.2	22.7	23.1		
	8H	14.1	14.6	14.5	15.0	15.4	21.8	22.3	22.2	22.7	23.1		
	12H	14.4	14.8	14.8	15.2	15.6	21.8	22.3	22.2	22.7	23.1		
8H	4H	13.7	14.2	14.1	14.6	15.0	21.7	22.2	22.1	22.6	23.0		
	6H	14.3	14.7	14.8	15.1	15.6	21.8	22.2	22.2	22.6	23.1		
	8H	14.7	15.0	15.2	15.5	16.0	21.8	22.2	22.3	22.6	23.1		
	12H	15.1	15.4	15.6	15.9	16.4	21.8	22.1	22.3	22.6	23.1		
	12H	4H	13.8	14.2	14.2	14.6	15.0	21.7	22.1	22.1	22.5	23.0	
		6H	14.5	14.8	15.0	15.3	15.8	21.8	22.1	22.2	22.6	23.0	
8H		14.9	15.2	15.4	15.7	16.2	21.8	22.1	22.3	22.6	23.1		
Variation of the observer position for the luminaire distances S													
S = 1.0H		+0.6 / -0.7					+2.0 / -2.2						
S = 1.5H		+1.1 / -1.2					+4.0 / -3.6						
S = 2.0H		+2.0 / -1.6					+5.8 / -5.1						
Standard table		BK04					BK01						
Correction summand		-5.4					1.4						
Corrected glare indices referring to 357lm Total luminous flux													

The UGR values are calculated in acc. with CIE Publ. 117. Spacing-to-Height-Ratio = 0.25